

## DF2.5S - Portable Outboard

Small in Size, Big in Performance

### SPECIFICATIONS

|                                   |                               |
|-----------------------------------|-------------------------------|
| Model                             | DF2.5                         |
| Engine Type                       | Water-cooled 4 stroke OHV     |
| Fuel Delivery System              | Carburator                    |
| Shaft Length mm                   | S:381 mm                      |
| Starting System                   | Manual                        |
| Weight kg                         | 13kg                          |
| No.of Cylinders                   | 1                             |
| Piston Displacement cm3           | 68cm3                         |
| Bore x Stroke mm                  | 48 x 38 mm                    |
| Maximum output kW (               | 1.8 kw                        |
| Full Throttle Operation Range rpm | 5250-5750                     |
| Steering                          | Tiller                        |
| Fuel Tank Capacity l              | Integral 1.0                  |
| Oil Pan Capacity in l             | 0.3                           |
| Ignition System                   | Pointless Electronic Ignition |
| Engine Mounting                   | Bushing Type                  |
| Trim Method                       | Manual                        |
| Gear Ratio                        | 2.15:1                        |
| Gear Shift                        | F-N                           |
| Exhaust                           | Above Prop Exhaust            |
| Propeller Size (in.)              | 7 3/8 x 5 3/8                 |

Meets the rigorous EPA2006 and CARB 3-Star Ultra Low emissions standards



# DF2.5S

## PRODUCT INFORMATION



# DF2.5S - Portable Outboard

## Small in Size, Big in Performance

The DF2.5S is the Lightest Suzuki 4-stroke motor built and generates plenty of power for small tenders and inflatables.

## Engine

- Pointless Electronic Ignition – easy-to-pull recoil starting
- Powerful power generation for small inflatables and tenders
- No battery required
- Simple and reliable
- Quiet and Smooth operation
- Water-cooled system promoting dependability
- 1 hour run time on a full tank
- Oil level indicator – easy check of oil levels



2.5HP single Cylinder OHV 4-stroke with 68cm<sup>3</sup>

## Handling

- Full size Grip – positive throttle control
- Upper bushing in collar – promotes smooth steady steering
- Adjustable steering and throttle tension
- F-N Shifting
- 360 degree steering



Twist-grip throttle and full-turn 360 steering

## Tilt and Carry Handle

- Easy-to-grip integrated handle
- Cowling within convenient reach
- Four tilt pin settings – match boat and prevailing conditions
- Fuel On/Off switch
- Balanced, lightweight, easy to manage

## Lightweight

- Easy transport and storage
- Weight – 13.5 kg
- Easy operation
- Easy maintenance

